

3-leg Chain Sling



Type: Master link MF, C-grab CG, C-grab Duo CGD, Chain KLA, Safety Hook GBK

Dim. mm	WLL t*		Total component length mm
	β 0-45° α 0-90°	β 45-60° α 90-120°	
6	3.1	2.2	311
8	5.2	3.7	392
10	8.4	6.0	474
13	14.0	10.0	604
16	21.0	15.0	680



Type: Master link MF, C-grab CG, C-grab Duo CGD, Chain KLA, Latch Hook EGKN

Dim. mm	WLL t*		Total Component length mm
	β 0-45° α 0-90°	β 45-60° α 90-120°	
6	3.1	2.2	306
8	5.2	3.7	357
10	8.4	6.0	444
13	14.0	10.0	559
16	21.0	15.0	634

4-leg Chain Sling



Type: Master link MF, C-grab Duo CGD, Chain KLA, Safety Hook GBK

Dim. mm	WLL t*		Total Component length mm
	β 0-45° α 0-90°	β 45-60° α 90-120°	
6	3.1	2.2	311
8	5.2	3.7	392
10	8.4	6.0	474
13	14.0	10.0	604
16	21.0	15.0	680



Type: Master link MF, C-grab Duo CGD, Chain KLA, Latch Hook EGKN

Dim. mm	WLL t*		Total Component length mm
	β 0-45° α 0-90°	β 45-60° α 90-120°	
6	3.1	2.2	306
8	5.2	3.7	357
10	8.4	6.0	444
13	14.0	10.0	559
16	21.0	15.0	634

WLL in tonnes, Grade 10 GrabiQ

1-leg		2-leg		3- & 4-leg		Choke hitch	
Chain dim.		β 0-45° α 0-90°	β 45-60° α 90-120°	β 0-45° α 0-90°	β 45-60° α 90-120°	β 0-45° α 0-90°	β 45-60° α 90-120°
6	1.5	2.1	1.5	3.15	2.24	1.6	1.2
7	2.0	1.8	2.0	4.2	3.0	2.2	1.6
8	2.5	3.5	2.5	5.2	3.7	2.7	2.0
10	4.0	5.6	4.0	8.4	6.0	4.4	3.2
13	6.7	9.5	6.7	14.0	10.0	7.4	5.3
16	10.0	14.0	10.0	21.0	15.0	11.0	8.0
20	16.0	22.4	16.0	33.6	24.0	17.6	12.8
22	20.0	28.0	20.0	42.0	30.0	22.0	16.0
26	27.0	38.2	27.0	57.3	40.5	29.7	21.6

Safety factor 4:1. Working load limits are based upon equally loaded and disposed sling legs.